



MOUNTING BRACKET (80X30X20)



MOUNTING BRACKET (130X30X30)



Description:

The Apex AP4 Pneumatic Positioner provides accurate valve positioning for Spring return and Double acting actuators. The compact, lightweight positioner also conforms to Namur VDI/VDE 3845 mounting standards and features a low profile visual position indicator. The modular design allows the addition of a wide range of feedback options including micro switches, inductive switches, gauges and position transmission. The positioner is mounted to the actuator using a NAMUR standard stainless steel mounting bracket.

Media :

Clean, dry, oil free air, filtered to 5 microns

General Specifications :

Enclosure Material: Aluminium alloy
 Enclosure Finish: Black epoxy paint
 Enclosure Rating: IP66
 Shaft Material: Stainless steel

Hysteresis: 0.8% Full Scale
 Linearity: 0.7% Full scale
 Sensitivity: 0.2% Of span
 Air Flow: 271 litres/min @5.5 bar
 Air Consumption: 8.7 litres/min @5.5 bar
 Control Input Signal: 3 - 15 psi
 Maximum supply pressure: 150 psi
 Air entry: 1/4"NPT
 Ambient temperature: -20°C - +80°C

Options:

- 4-20mA Control
- Pressure gauges
- 4-20mA 2 wire position transmitter
- Mechanical switches
- Inductive switches